





1\*

1

See Section 8

#### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Region:

Product name: Medium Strength Threadlocker Blue Automotive

Grade

Product type: Anaerobic Sealant

Company address: Henkel Corporation 1001 Trout Brook Crossing Rocky Hill, Connecticut 06067 Item number: 24200

Contact Information: Telephone: 860.571.5100

Emergency telephone: 860.571.5100

United States

Internet: www.loctite.com

# 2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components Polyglycol dimethacrylate 25852-47-5	<u>%</u> 60-100	ACGIH TLV None	<u>OSHA PEL</u> None	<u>OTHER</u> None
Polyglycol oleate 9004-96-0	10-30	None	None	None
Saccharin 81-07-2	1-5	None	None	None
Silica, amorphous, fumed, crystalline-free 112945-52-5	1-5	6 mg/m³ TWA	10 mg/m³ TWA	3 mg/m³ TWA respirable dust
Cumene hydroperoxide 80-15-9	1-5	None	None	1 ppm (6 mg/m³) Skin (WEEL)
Propylene glycol 57-55-6	1-5	None	None	None

# 3. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

HMIS:

 Physical state:
 Liquid
 HEALTH:

 Color:
 Blue
 FLAMMABILITY:

 Odor:
 Mild
 PHYSICAL HAZARD:

 Personal Protection:

**WARNING:** CAUSES EYE IRRITATION.

MAY CAUSE SKIN IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

**Inhalation:** May cause respiratory tract irritation.

**Skin contact:** May cause allergic skin reaction. May cause skin irritation.

**Eye contact:** Contact with eyes will cause irritation. **Ingestion:** Not expected to be harmful by ingestion.

Item number: 24200 Product name: Medium Strength Threadlocker Blue Automotive Grade

Existing conditions aggravated by exposure:

Eye, skin, and respiratory disorders.

See Section 11 for additional toxicological information.

# 4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If symptoms develop and persist, get medical attention.

Skin contact: Wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse.

Get medical attention if symptoms occur.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding

eyelids open all the time. Get medical attention.

Ingestion: Do not induce vomiting. Keep individual calm. Obtain medical attention.

#### 5. FIRE-FIGHTING MEASURES

Flash point: Greater than 93°C (200°F) Tagliabue closed cup

Autoignition temperature: Not available

Flammable/Explosive limits-lower %: 2.6 % (propylene glycol)

Flammable/Explosive limits-upper %: 12.5 % (propylene glycol)

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special fire fighting procedures: None

Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapors.

# 6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Prevent product from entering drains or open waters.

Clean-up methods: Soak up with inert absorbent. Store in a partly filled, closed container until disposal.

# 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after

handling.

Storage: For safe storage, store at or below 38°C (100°F), Keep in a cool, well ventilated area away from heat,

sparks and open flame. Keep container tightly closed until ready for use.

Incompatible products: Refer to Section 10.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls: No specific ventilation requirements noted, but forced ventilation may still be required if concentrations

exceed occupational exposure limts.

Item number: 24200 Product name: Medium Strength Threadlocker Blue Automotive Grade

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact. Neoprene

gloves. Butyl rubber gloves. Natural rubber gloves.

**Eye/face protection:** Safety goggles or safety glasses with side shields.

See Section 2 for exposure limits.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid
Color: Blue
Odor: Mild

Vapor pressure: Less than 5 mm Hg at 27°C (80°F)

pH: Not applicable

Boiling point/range: Greater than 149°C (300°F)

Melting point/range:Not availableSpecific gravity:1.1 at 23.9°C (75°F)Vapor density:Not availableEvaporation rate:Not availableSolubility in water:Slight

VOC content: 4.48%; 49.3 grams/liter (EPA Method 24)

Not available

### 10. STABILITY AND REACTIVITY

Stability: Stable.

Partition coefficient (n-octanol/water):

Hazardous polymerization: Will not occur.

Hazardous decomposition products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapors.

Incompatability: Strong oxidizers. Free radical initiators. Strong reducing agents. Alkalis. Oxygen scavengers. Other

polymerization initiators. Copper. Iron. Zinc. Aluminum. Rust.

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatability" (Section 10).

# 11. TOXICOLOGICAL INFORMATION

Product toxicity data: Acute oral LD50 greater than 10, 000 mg/kg (rat). Acute dermal LD50 greater than 5000 mg/kg (rabbit).

### Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Polyglycol dimethacrylate	No	No	No
Polyglycol oleate	No	No	No
Saccharin	No	No	No
Silica, amorphous, fumed, crystalline-free	No	No	No
Cumene hydroperoxide	No	No	No
Propylene glycol	No	No	No

### Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs		
Polyglycol dimethacrylate	Allergen, Irritant		
Polyglycol oleate			
Saccharin	No Target Organs		
Silica, amorphous, fumed, crystalline-free	Nuisance dust		
Cumene hydroperoxide	Allergen, Central nervous system, Corrosive, Irritant, Mutagen		
Propylene glycol	Irritant		

Item number: 24200 Product name: Medium Strength Threadlocker Blue Automotive Grade

#### 12. ECOLOGICAL INFORMATION

Ecological information: Not available

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

**EPA hazardous waste number:**Not a RCRA hazardous waste.

### 14. TRANSPORT INFORMATION

# U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Unrestricted Hazard class or division: None Identification number: None Packing group: None

# International Air Transportation (ICAO/IATA):

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None
Packing group: None

### WaterTransportation (IMO/IMDG):

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None
Packing group: None
Marine pollutant: None

# 15. REGULATORY INFORMATION

#### United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: None.

CERCLA/SARA Section 302 EHS: None above reporting de minimus.

CERCLA/SARA Section 311/312: Immediate Health Hazard, Delayed Health Hazard

CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313

of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Cumene

hydroperoxide (CAS# 80-15-9) .

California Proposition 65: This product contains a chemical known to the State of California to cause cancer and birth defects or

other reproductive harm. 1,4-Dioxane (CAS# 123-91-1). Ethylene oxide (CAS# 75-21-8). Arsenic

(CAS# 7440-38-2). Lead (CAS# 7439-92-1).

#### Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Domestic Substances List.

WHMIS hazard class: D.2.A, D.2.B

Item number: 24200 Product name: Medium Strength Threadlocker Blue Automotive Grade

4 of 5

#### 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: Expanded chemical information in Section 2 and related sections.

Prepared by:

Item number:

24200

Kyra Kozak Woods, Health and Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Product name: Medium Strength Threadlocker Blue Automotive Grade

5 of 5